

SAKO SPECIFICATION SAKO

SAKO 75 FINNLIGHT



SAKO 75 FINNLIGHT has a series of actions which are designated: Medium actions III and SM, Long actions IV and V (Magnum). All metal parts are made of stainless steel or are specially coated to ensure excellent wear and corrosion resistance in different weather conditions. Magazine bottom and trigger guard are made of hard anodized aluminium for reduced weight.

The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection; integral tapered scope mount rail and one-piece forged bolt.

Bolts are optionally available provided with KEY CONCEPT locking system to prevent illicit use.

The MAGAZINE is detachable and it can also be loaded through the ejection port.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

The STOCK is made by injection molding in two steps so that the grip areas in the pistol grip and fore-end are made of a softer material.

Sako 75 Finnlight is supplied WITHOUT OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver.

The short, fluted, totally free-floating, stainless steel BARREL is cold-hammerforged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
III	243 Win	10"	III	1035 mm (40 3/4")
	260 Rem	9"	SM	1140 mm (44 7/8")
	7mm-08 Rem	9.5"	IV	1060 mm (41 3/4")
	308 Win	11"	V	1160 mm (45 5/8")
SM	270 Win Short Mag	10"	Barrel length	
	300 Win Short Mag	11"	III	515 mm (20 1/4")
IV	25-06 Rem	10"	IV	530 mm (20 7/8")
	6.5x55 SE	8"	V / SM	620 mm (24 3/8")
	270 Win	10"	Weight	
V	30-06 Sprg	11"	III	2.8 kg (6 1/4 lbs)
	7mm Rem Mag	9.5"	SM	3.0 kg (6 5/8 lbs)
Cartridge capacity			IV	3.1 kg (6 7/8 lbs)
III / IV 6 rounds (1 in chamber, 5 in magazine)			V	3.3 kg (7 1/4 lbs)
V / SM 5 rounds (1 in chamber, 4 in magazine)				