

sako**SPECIFICATION****sako****SAKO 75 HUNTER
LEFTHAND**

SAKO 75 HUNTER LEFTHAND has a series of totally lefthanded actions which are designated: Long action IV.

The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection; integral tapered scope mount rail and one-piece forged bolt.

Bolt is optionally available provided with KEY CONCEPT locking system to prevent illicit use.

The MAGAZINE is detachable and it can also be loaded through the ejection port.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

The walnut STOCK is oilfinished as standard. Matte-lacquered stocks are also available.

Open sights with post bead are adjustable for windage. Optionally available also without open sights. Integral rails for the scope mounts are on the top of the receiver.

The totally free-floating BARREL is cold hammer-forged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
IV	25-06 Rem	10"	IV	1110 mm (43 3/4")
	6.5x55 SE	8"	Barrel length	
	270 Win	10"	IV	580 mm (22 7/8")
	7x64	10"	Weight	
	30-06 Sprg	11"	IV	3.6 kg (7 15/16 lbs)
	9.3x62	14"	Cartridge capacity	
9.3x66 Sako	14"		IV 6 rounds (1 in chamber, 5 in magazine)	

sako

SPECIFICATION

sako

SAKO 75 HUNTER LEFTHAND



SAKO 75 HUNTER LEFTHAND has a series of totally lefthanded actions which are designated: Long action IV. The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection; integral tapered scope mount rail and one-piece forged bolt. Bolt is optionally available provided with KEY CONCEPT locking system to prevent illicit use. The MAGAZINE is detachable and it can also be loaded through the ejection port. The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged. The walnut STOCK is matte-lacquered. Oil finish available as special order. Models are available WITHOUT OPEN SIGHTS. Open sights with post bead are adjustable for windage. Available as special order. Integral rails for the scope mounts are on the top of the receiver. Standard size blued Sako Optilock scope mounts included with the rifle. The totally free-floating BARREL is cold hammer-forged. Sling swivels standard.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
IV	25-06 Rem	10"	IV	1110 mm (43 3/4")
	6.5x55 SE *	8"	Barrel length	
	270 Win	10"	IV	580 mm (22 7/8")
	7x64 *	10"	Weight	
	30-06 Sprg	11"	IV	3.6 kg (7 15/16 lbs)
	9.3x62 *	14"	Cartridge capacity	
9.3x66 Sako *	14"		IV 6 rounds (1 in chamber, 5 in magazine)	
	* Special order only			