

SAKO SPECIFICATION SAKO

SAKO 75 VARMINT



SAKO 75 VARMINT has a series of actions which are designated: Short action I and Medium action III. The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection; integral tapered scope mount rail and one-piece forged bolt. Medium bolts are optionally available provided with KEY CONCEPT locking system to prevent illicit use. The MAGAZINE is detachable and it can also be loaded through the ejection port. The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option. The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged. The walnut STOCK is oilfinished as standard. Mattelacquered stocks are also available. SAKO 75 VARMINT is supplied WITHOUT OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. The heavy, totally free-floating BARREL is cold-hammerforged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length
I	222 Rem	14"	I 1100 mm (43 1/4")
	223 Rem	8"	III 1120 mm (44")
III	22-250 Rem	14"	Barrel length
	243 Win	10"	I - III 600 mm (23 5/8")
	260 Rem	9"	Weight
	7mm-08 Rem	9.5"	I 3.7 kg (8 1/8 lbs)
	308 Win	11"	III 3.9 kg (8 5/8 lbs)
			Cartridge capacity
			I 7 rounds (1 in chamber, 6 in magazine)
			III 6 rounds (1 in chamber, 5 in magazine)