

SAKO SPECIFICATION SAKO

SAKO 75 VARMINT LAMINATED STAINLESS



SAKO 75 VARMINT LAMINATED STAINLESS has a series of actions which are designated: Short action I and Medium action III. All metal parts are made of stainless steel or are specially coated to ensure excellent wear and corrosion resistance in different weather conditions.

The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection; integral tapered scope mount rail and one-piece forged bolt.

Medium bolts are optionally available provided with KEY CONCEPT locking system to prevent illicit use.

The MAGAZINE is detachable and it can also be loaded through the ejection port.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

The hardwood laminated brown STOCK is mattelacquered.

SAKO 75 VARMINT LAMINATED STAINLESS is supplied WITHOUT OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver.

The heavy, fluted, stainless steel, totally free-floating BARREL is cold-hammerforged. Available also with unfluted barrel as option.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
I	222 Rem	14"	I	1100 mm (43 1/4")
	223 Rem	8"	III	1120 mm (44")
III	22-250 Rem	14"	Barrel length	
	243 Win	10"	I - III	600 mm (23 5/8")
	260 Rem	9"	Weight	
	7mm-08 Rem	9.5"	I	3.9 kg (8 5/8 lbs)
	308 Win	11"	III	4.1 kg (9 lbs)
			Cartridge capacity	
			I	7 rounds (1 in chamber, 6 in magazine)
			III	6 rounds (1 in chamber, 5 in magazine)