

# SAKO SPECIFICATION SAKO

## SAKO FINNFIRE RANGE



SAKO FINNFIRE RANGE rimfire rifle based on P94S action.

The ACTION is a bolt action design with two locking lugs, bolt lift angle 50°, bolt throw 30 mm (1.20 in) and firing pin travel 5 mm (0.20 in). Ejection is carried out with special spring.

The MAGAZINE is 10-shot clip magazine in cal 22 LR.

The TRIGGER is the same single-stage trigger as on other Sako-rifles. Adjustable from 1 to 2 kg (2 - 4 lbs).

Sliding SAFETY catch located rear from the bolt handle locks the trigger and the bolt.

The oilfinished STOCK is made of walnut and has an adjustable cheek piece and butt-plate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers and the butt plate is also infinitely adjustable in height and pitch.

Sako Finnfire Range is supplied without OPEN SIGHTS. 11 mm integral dovetail for scope mounting.

The heavy, free-floating BARREL is formed by the cold-hammering process. Barrel with thread 1/2"-20 UNF at the muzzle for silencer mounting as option.

### TECHNICAL DATA

#### Caliber and rate of twist

22 LR    420 mm    16.5"

#### Overall length

P94S    1025 mm    40 1/2"

#### Barrel length

P94S    585 mm    23"

#### Weight

P94S    3.4 kg    7 1/2 lbs