

sako SPECIFICATION sako

SAKO FINNFIRE VARMINT



SAKO FINNFIRE VARMINT rimfire rifle based on P94S action.

The ACTION is a bolt action design with two locking lugs, bolt lift angle 50°, bolt throw 30 mm (1.20 in) and firing pin travel 5 mm (0.20 in). Ejection is carried out with special spring.

The MAGAZINE is 5-shot clip magazine in cal 22 LR. 10-shot clip magazine is also available.

The TRIGGER is the same single-stage trigger as on other Sako-rifles. Adjustable from 1 to 2 kg (2 - 4 lbs). Also available with single set trigger mechanism as option.

Sliding SAFETY catch, located rear from the bolt handle, locks the trigger and the bolt.

The Sako 75 style walnut STOCK is oilfinished as standard. Mattlacquered stocks are also available. The length of pull and the buttplate angle are adjustable by means of straight and angled spacers.

Sako Finnfire Varmint is supplied WITHOUT OPEN SIGHTS. 11 mm integral dovetail for scope mounting.

The heavy, free-floating BARREL is formed by the cold-hammering process. Barrel with thread 1/2"-20 UNF at the muzzle for silencer mounting as option.

TECHNICAL DATA

Caliber and rate of twist

22 LR	420 mm	16.5"
-------	--------	-------

Weight

P94S	3.3 kg	7 1/4 lbs
------	--------	-----------

Overall length

P94S	1025 mm	40 1/2"
------	---------	---------

Barrel length

P94S	585 mm	23"
------	--------	-----