



SPECIFICATION



TIKKA MASTER CONTINENTAL



TIKKA MASTER CONTINENTAL has a series of actions which are designated: Short action M595, Long action M695 incl. Magnum. Bolt handle is stainless steel.

The detachable clip MAGAZINE holds 4-6 cartridges, depending on caliber. 3-shot extra magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The walnut STOCK with extra wide fore-end is oilfinished as standard and has a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Matte-lacquered stocks are also available. Features palm swell.

TIKKA MASTER CONTINENTAL is supplied without OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating BARREL is cold-hammerforged. On special order rifles can also be supplied with stainless steel barrel.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
M595	17 Rem	10"	M595	1110 mm (43 3/4")
	222 Rem	14"	M695	1120 mm (44")
	223 Rem	12"	M695 Mag	1120 mm (44")
	22-250 Rem	14"	Barrel length	
	243 Win	10"	M595	600 mm (23 3/8")
	7mm-08 Rem	9.5"	M695	600 mm (23 3/8")
	308 Win	11"	M695 Mag	600 mm (23 3/8")
M695	25-06 Rem	10"	Weight	
	6.5x55 SE	8"	M595	3.7 kg (8 1/8 lbs)
	270 Win	10"	M695	3.8 kg (8 3/8 lbs)
	7x64	10"	M695 Mag	3.8 kg (8 3/8 lbs)
	30-06 Sprg	11"	Cartridge capacity	
M695 Mag	9.3x62	14"	M595	6 rounds (1 in chamber, 5 in clip magazine)
	7 mm Rem Mag	9.5"	M695	6 rounds (1 in chamber, 5 in clip magazine)
	300 Win Mag	11"	M695 Mag	5 rounds (1 in chamber, 4 in clip magazine)
	338 Win Mag	10"		



SPECIFICATION



TIKKA CONTINENTAL



TIKKA CONTINENTAL has a series of actions which are designated: Short action M595, Long action M695 incl. Magnum. Bolt handle is stainless steel.

The detachable clip MAGAZINE holds 4-6 cartridges, depending on caliber. 3-shot extra magazine is available as accessory.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs).

The walnut STOCK with extra wide fore-end is mottled and has a buttplate system where the length of pull and the butt plate angle are adjustable by means of straight and angled spacers. Features palm swell.

TIKKA CONTINENTAL is supplied without OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard scope mount bases.

The free-floating BARREL is cold-hammerforged. On special order rifles can also be supplied with stainless steel barrel.

Sling swivels standard.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length
M595	17 Rem	10"	M595 1110 mm (43 3/4")
	222 Rem *	14"	M695 1120 mm (44")
	223 Rem	12"	M695 Mag 1120 mm (44")
	22-250 Rem	14"	Barrel length
	243 Win	10"	M595 600 mm (23 3/8")
	7mm-08 Rem	9.5"	M695 600 mm (23 3/8")
	308 Win	11"	M695 Mag 600 mm (23 3/8")
M695	25-06 Rem	10"	Weight
	6.5x55 SE *	8"	M595 3.7 kg (8 1/8 lbs)
	270 Win	10"	M695 3.8 kg (8 3/8 lbs)
	7x64 *	10"	M695 Mag 3.8 kg (8 3/8 lbs)
	30-06 Sprg	11"	Cartridge capacity
9.3x62 *	14"	M595 6 rounds (1 in chamber, 5 in clip magazine)	
M695 Mag	7 mm Rem Mag	9.5"	M695 6 rounds (1 in chamber, 5 in clip magazine)
	300 Win Mag	11"	M695 Mag 5 rounds (1 in chamber, 4 in clip magazine)
	338 Win Mag	10"	

* Special order only