

PUGIO V

SHORT IS BETTER.

Victrix Pugio is the most compact system in our catalogue, designed for urban sniping. Lighter, easier to carry, and designed following the specific needs of special forces: small dimensions and concealed transport. No one says you need a bigger rifle to hit your target.



PUGIO V DATA SHEET

Destination use

Law Enforcement Military Sporting

Caliber

.308 Win. (1/10)

Barrel length

16″

Weight

5.7 kg (12.57 lb) with an empty magazine, muzzle brake, barrel length 16" and no scope

Dimension

Closed overall length: 714 mm (28.11") Open overall length: 960 mm (37.80") With muzzle brake and barrel length 16"

Base rifle

Benchmark lapped match-grade button rifled barrel in AISI 416R Barrel muzzle thread M18x1mm

Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine

adjustment, and an insulated cheek piece

Single feed and single stack 7-round magazine

Reversible EVO button folding system

Octagonal elliptic forend with M-LOK® system, a 20 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913 Ergonomic and interchangeable zero angle flat top grip for standard AR platform

20 MoA action rail according to STANAG 4694/Mil std 1913 Detachable multifunction carry handle with quick mount:

- with QM (Quick mount) attachment for picatinny rail
- ergonomic handle
- integrated picatinny rail
- hook for rope attachment
- · QD (Quick detach) attachments
- tripod attachment with 1/4" 20 UNC and 3/8" 16 UNC threads
- front magnetic bit holder for field maintenance

Victrix ProAngle detachable muzzle brake featuring 3 forward-canted chambers

Short action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machinery. Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105 degree lift, dirt/ice grooves integral PVD finish on the action and on the bolt Victrix Professional Dual-stage trigger, convertible to a single stage

trigger, with two positions top safety: standard setting approx. 1000 gr (35.27 oz)

Explorer Cases case for transport cod. 7814 User manual and welcome kit



Every and each component made of light alloy undergoes a hard black anodising CERAKOTE ceramic polymer firearm coatings available in three colours: Dark Grey Dark Olive Drab Green Medium Flat Brown

Optional

Side picatinny rails for forend with M-LOK® system according to STANAG 4694/Mil std 1913





